



Lokong Bearing Co., Ltd.



20 mm x 47 mm x 14 mm GIKL16-PW Rod End Bearing With Left Hand Thread

Bearing No. 6204

6204 Bearing 2D drawings and 3D CAD models

Size	20x47x14 mm
Bore Diameter	20 mm
Outer Diameter	47 mm
Width	14 mm
d	20 mm
D	47 mm
B	14 mm
C	14 mm
r min.	1 mm
da min.	25 mm
da max	26,5 mm
Da max.	42 mm
ra max.	1 mm
Weight	0,107 Kg
Basic dynamic load rating (C)	12,8 kN
Basic static load rating (C0)	6,6 kN
(Grease) Lubrication Speed	15 000 r/min
(Oil) Lubrication Speed	18 000 r/min
Category	Single Row Ball Bearings
Inventory	6.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.1
EAN	0029176014215
Product Group	B00308



Lokong Bearing Co., Ltd.

Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	20MM Bore; 47MM Outside Diameter; 14MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.nskamericas.com
Manufacturer Item Number	6204
Weight / LBS	0.23
Bore	0.787 Inch 20 Millimeter
Outside Diameter	1.85 Inch 47 Millimeter
Outer Race Width	0.551 Inch 14 Millimeter
bore diameter:	20 mm
closure type:	Open
outside diameter:	47 mm
internal clearance:	Normal Clearance
overall width:	14 mm
manufacturer upc number:	029176014215



Lokong Bearing Co., Ltd.

bore type:	Round
SRI	4.01
hidYobi	6204
LangID	1
D_	47
SREX	0.04
B_	14
da min	25
hidTable	ecat_NSRDGB
Oil rpm	18000
SRE	4.21
mass	0.107
GRS rpm	15000
ra	1
SRIX	0.02
D_a	42
SRIN	0
C0	6.6
fo	13.1
SREN	0
DE_	41.438
Prod_Type3	DGBB_SR_OT
DA_	7.938
bomp	0
Z_	8
yobi	6204
C_conv	12800
ALPHA_	0
SDM_	33.5
r	1
KBRG	6101
SBRG	2



Lokong Bearing Co., Ltd.

DI_	25.562
-----	--------